

The Public Health and Safety Organization

NSF Product and Service Listings

These NSF Official Listings are current as of **Friday, August 19, 2022** at 12:15 a.m. Eastern Time. Please <u>contact NSF</u> to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information: http://info.nsforg/Certified/PwsComponents/Listings.asp?Company=0C660&Standard=o618z

NSF/ANSI/CAN 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of <u>Abbreviations used in these Listings.</u> Click here for the definitions of <u>Water Contact Temperatures denoted in these Listings.</u>

Kryton International Inc.

1645 East Kent Avenue Vancouver, BC V5P 288 Canada 800-267-8280 604-324-8280

Facility: Vancouver, British Columbia, Canada

Protective (Barrier) Materials

| Trade Designation | Water Contact Size Restriction | Water Contact Temp | Water Contact Material |
|-----------------------------|-----------------------------------|--------------------------|------------------------------|
| Concrete Admixtures | | | |
| KIM-AE | [1] | C. HOT | CMNT |
| KIM-ES | D.] | C. HOT | CMNT |
| KIM-HS | [1] | C. HOT | CMNT |
| Krystol Internal Membrane | [¹] | C. HOT | CMNT |
| Krystol Repair Grout | [¹] | C. HOT | CMNT |
| Krystol Ti | [I] | C. HOT | CMNT |
| Krystol T2 | DJ | C. HOT | CMNT |
| Krystol Waterstop Grout | [1] | C. HOT | CMNT |
| Krystol Waterstop Treatment | [¹ -] | C. HOT | CMNT |

[1] Certified for use in tanks 6000 gallons and greater. Maximum use level of admixture is 2% of cement by mass.

Number of matching Manufacturers is I

Number of matching Products is 9

Processing time was o seconds